

E25. Noise and vibration

E25.1. Background

Noise and vibration may cause adverse effects on amenity depending on:

- when and where it occurs;
- its duration;
- physical characteristics, including the sound pressure level (loudness) and frequency (pitch);
- its steadiness;
- variations of these properties; and
- whether special audible characteristics are present.

Within urban areas, the background noise environment is most often dominated by traffic. Generally, the higher the traffic volumes nearby, the higher the background noise level. In low traffic areas, background noise may occur naturally from waves, high winds, animals or insects. The Plan cannot control either traffic noise or natural noise.

The objectives and policies for noise and vibration seek to control the levels of noise and vibration created by activities to limit the adverse effects of noise and vibration on amenity values, human health and to protect existing noisy activities from reverse sensitivity effects.

E25.2. Objectives [rcp/dp]

- (1) People are protected from unreasonable levels of noise and vibration.
- (2) The amenity values of residential zones are protected from unreasonable noise and vibration, particularly at night.
- (3) Existing and authorised activities and infrastructure, which by their nature produce high levels of noise, are appropriately protected from reverse sensitivity effects where it is reasonable to do so.
- (4) Construction activities that cannot meet noise and vibration standards are enabled while controlling duration, frequency and timing to manage adverse effects.

E25.3. Policies [rcp/dp]

- (1) Set appropriate noise and vibration standards to reflect each zone's function and permitted activities, while ensuring that the potential adverse effects of noise and vibration are avoided, remedied or mitigated.
- (2) Minimise, where practicable, noise and vibration at its source or on the site from which it is generated to mitigate adverse effects on adjacent sites.

- (3) Encourage activities to locate in zones where the noise generated is compatible with other activities and, where practicable, adjacent zones.
- (4) Use area or activity specific rules where the particular functional or operational needs of the area or activity make such rules appropriate.
- (5) Prevent significant noise-generating activities other than roads and railway lines from establishing in or immediately adjoining residential zones.
- (6) Avoid activities sensitive to noise from establishing in industrial zones where adverse effects (including reverse sensitivity effects) arise that cannot be otherwise appropriately remedied or mitigated.
- (7) Require activities to be appropriately located and/or designed to avoid where practicable or otherwise remedy or mitigate reverse sensitivity effects on:
 - (a) existing or authorised infrastructure;
 - (b) adjacent Business – Light Industry Zone and Business – Heavy Industry Zone;
 - (c) existing lawfully established rural production activities;
 - (d) major recreation facilities;
 - (e) existing lawfully established commercial activities within Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone, Business – Local Centre Zone, Business – Neighbourhood Centre Zone, Business – Mixed Use Zone; or
 - (f) regionally significant mineral extraction activities.

Noise arising from lakes, rivers and the coastal marine area

- (8) Require activities to be insulated or protected, from unreasonable manmade noise and vibration emitted from the use and development of neighbouring lakes, rivers or the coastal marine area.

Noise arising from or affecting rural zones

- (9) Avoid, remedy or mitigate the adverse effects of noise in the rural environment, having regard to the working nature of this environment.

Construction, demolition and maintenance activities

- (10) Avoid, remedy or mitigate the adverse effects of noise and vibration from construction, maintenance and demolition activities while having regard to:
 - (a) the sensitivity of the receiving environment; and
 - (b) the proposed duration and hours of operation of the activity; and

(c) the practicability of complying with permitted noise and vibration standards.

Events and activities

- (11) Recognise that activities occurring in the Open Space – Sport and Active Recreation Zone may generate high levels of noise and ensure that adverse effects are avoided, remedied or mitigated having regard to the sensitivity of the receiving environment.

E25.4. Activity table

Table E25.4.1 Activity table specifies the activity status of land use and development activities pursuant to section 9(3) of the Resource Management Act 1991 and the activity status of coastal use, occupation and activity pursuant to sections 12(1); 12(2) and 12(3) of the Resource Management Act 1991.

Table E25.4.1 Activity table

Activity		Activity status
(A1)	Activities that comply with all the relevant permitted activity standards	P
(A2)	Activities that do not comply with a permitted activity standard	RD

E25.5. Notification

- (1) Any application for resource consent for an activity listed in Table E25.4.1 Activity table will be subject to the normal tests for notification under the relevant sections of the Resource Management Act 1991.
- (2) When deciding who is an affected person in relation to any activity for the purposes of section 95E of the Resource Management Act 1991 the Council will give specific consideration to those persons listed in Rule C1.13(4).

E25.6. Standards

All activities must comply with the following relevant permitted activity standards.

E25.6.1. General standards

- (1) Noise levels arising from activities must be measured and assessed in accordance with the New Zealand Standard NZS 6801:2008 Measurement of environmental sound and the New Zealand Standard NZS 6802:2008 Acoustics - Environmental noise except where more specific requirements apply.
- (2) The application of an adjustment for noise containing special audible characteristics in terms of Appendix B4 Special Audible Characteristics in New Zealand Standard NZS 6802:2008 Acoustics – Environmental noise may apply to the A weighted level for any measurement but an adjustment must not be applied to any level measured in the 63Hz and 125Hz octave bands.

- (3) The noise from any construction work activity must be measured and assessed in accordance with the requirements of New Zealand Standard NZS6803:1999 Acoustics – Construction noise. Construction work is defined in New Zealand Standard NZS6803:1999 Acoustics – Construction noise.
- (4) The noise limits of the Plan do not apply to emergency service sirens and callout sirens during emergency situations.
- (5) Where more than one standard applies that requires insulation of a noise-sensitive space from an external noise source, the standards must be applied cumulatively.
- (6) Where standards are provided for specific activities, the zone interface standards and the zone standards do not apply to that activity.

Noise levels arising from activities within zones

E25.6.2. Maximum noise levels in residential zones

- (1) The noise (rating) levels and maximum noise level arising from any activity in the Residential – Large Lot Zone, Residential – Rural and Coastal Settlement Zone, Residential – Single House Zone, Residential – Mixed Housing Suburban Zone, Residential – Mixed Housing Urban Zone and the Residential – Terrace Housing and Apartment Buildings Zone measured within the boundary of an adjacent site in these residential zones must not exceed the levels in Table E25.6.2.1 Noise levels in residential zones below:

Table E25.6.2.1 Noise levels in residential zones

Time	Noise level
Monday to Saturday 7am-10pm	50dB L _{Aeq}
Sunday 9am-6pm	
All other times	40dB L _{Aeq} 75dB L _{AFmax}

- (2) The levels for the daytime hours in Table E25.6.2.1 Noise levels in residential zones may be exceeded by intermittent noise for reasonable periods where that noise is associated with normal household activities, such as lawn mowing or home handyman work.

E25.6.3. Noise levels in rural and future urban zones

- (1) The noise (rating) level from any activity in the Rural – Mixed Rural Zone, Rural – Rural Production Zone, Rural – Rural Coastal Zone or the Future Urban Zone measured within the notional boundary on any site in any rural zone must not exceed the limits in Table E25.6.3.1 Noise levels in the Rural – Mixed Rural Zone, Rural – Rural Production Zone, Rural – Rural Coastal Zone or the Future Urban Zone below:

Table E25.6.3.1 Noise levels in the Rural – Mixed Rural Zone, Rural – Rural Production Zone, Rural – Rural Coastal Zone or the Future Urban Zone

Time	Noise level
Monday to Saturday 7am-10pm	55dB L _{Aeq}
Sunday 9am-6pm	
All other times	45dB L _{Aeq} 75dB L _{AFmax}

- (2) The noise (rating) level from any activity in the Rural – Rural Conservation Zone; Rural – Countryside Living Zone, Rural – Waitākere Foothills Zone; or the Rural – Waitākere Ranges Zone measured within the notional boundary on any site in any rural zone must not exceed the limits in Table E25.6.3.2 Noise levels in the Rural – Rural Conservation Zone, Rural – Countryside Living Zone, Rural – Waitākere Foothills Zone; or Rural – Waitākere Ranges Zone below:

Table E25.6.3.2 Noise levels in the Rural – Rural Conservation Zone Countryside Living Zone, Rural – Waitākere Foothills Zone; or the Rural – Waitākere Ranges Zone

Time	Noise level
Monday to Saturday 7am-10pm	50 dB L _{Aeq}
Sunday 9am-6pm	
All other times	40 dB L _{Aeq} 75 dB L _{AFmax}

- (3) Standards E25.6.3(1) and E25.6.3(2) above do not apply to any of the following:
- (a) animal noise on farms unless they are confined within a building or enclosure on a permanent or semi-permanent basis;
 - (b) the use of mobile agricultural horticultural or forestry vehicles or machinery, or other mobile or portable agricultural, horticultural or forestry equipment; and

Note 1

The operator of such vehicles or machinery is required by the Resource Management Act 1991 to adopt the best practicable option to ensure that noise emissions do not exceed a reasonable level, which will depend on the time they are used, how loud they are, how long it is used for and how often it is used near rural dwellings.

- (c) the use of post-harvest facilities including vehicle access ways and milking sheds set back at least 100m from a notional boundary.

E25.6.4. Bird scaring devices in the Rural – Mixed Rural Zone, Rural – Rural Production Zone, Rural – Rural Coastal Zone and the Future Urban Zone

- (1) Bird scaring or bird repelling devices in the in the Rural – Mixed Rural Zone, Rural – Rural Production Zone, Rural – Rural Coastal Zone and the Future Urban Zone must not operate:
 - (a) between the hours of sunset and sunrise; and
 - (b) at a frequency of more than six times in any 60-minute period with no more than three shots in rapid succession; and
 - (c) where the noise level measured within the notional boundary on any other site exceeds 85dB L_{Zpeak} .
- (2) Standard E25.6.4(1) above does not apply to bird scaring devices that generate a noise level less than 70 dB L_{Zpeak} measured at the notional boundary on another site.

E25.6.5. Noise levels in the Business – Heavy Industry Zone or the Business – Light Industry Zone

- (1) The noise (rating) level arising from an activity in the Business – Heavy Industry Zone or the Business – Light Industry Zone measured within the boundary of any other site in those zones must not exceed the limits in Table E25.6.5.1 Noise levels in the Business – Heavy Industry Zone or the Business – Light Industry Zone below:

Table E25.6.5.1 Noise levels in the Business – Heavy Industry Zone or the Business – Light Industry Zone

Time	Business – Heavy Industry Zone	Business – Light Industry Zone
All times	70dB L_{Aeq}	65dB L_{Aeq}

E25.6.6. Noise levels in the Business – General Business Zone or the Business – Business Park Zone

- (1) The noise (rating) level arising from an activity in the Business – General Business Zone or the Business – Business Park Zone measured within the boundary of any other site in those zones must not exceed the limits in Table E25.6.6.1 Noise levels in the Business – General Business Zone and the Business – Business Park Zone below:

Table E25.6.6.1 Noise levels in the Business – General Business Zone or the Business – Business Park Zone

Time	Business – General Business Zone	Business – Business Park Zone
All times	65dB L _{Aeq}	60dB L _{Aeq}

E25.6.7. Noise levels in the Business – Local Centre Zone or the Business – Neighbourhood Centre Zone

- (1) The noise (rating) level and maximum noise level arising from any activity in the Business – Local Centre Zone or the Business – Neighbourhood Centre Zone measured or assessed as the incident level on the façade of any building on any other site in the Business – Local Centre Zone or the Business – Neighbourhood Centre Zone must not exceed the levels in Table E25.6.7.1 Noise levels in the Business – Local Centre Zone or the Business – Neighbourhood Centre Zone below:

Table E25.6.7.1 Noise levels in the Business – Local Centre Zone or the Business – Neighbourhood Centre Zone

Time	Business – Local Centre Zone	Business – Neighbourhood Centre Zone
7am - 10pm	60dB L _{Aeq}	60dB L _{Aeq}
10pm - 7am	50dB L _{Aeq} 60dB at 63 Hz L _{eq} 55dB at 125 Hz L _{eq} 75dB L _{AFmax}	50dB L _{Aeq} 60dB at 63 Hz L _{eq} 55dB at 125 Hz L _{eq} 75dB L _{AFmax}

E25.6.8. Noise levels in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone or the Business – Mixed Use Zone

- (1) The noise (rating) level and maximum noise level arising from any activity in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone or the Business – Mixed Use Zone measured or assessed as the incident level on the façade of any building on any other site in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone or the Business – Mixed Use Zone must not exceed the limits in Table E25.6.8.1 Noise levels in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone or the Business – Mixed Use Zone below:

Table E25.6.8.1 Noise levels in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone or the Business – Mixed Use Zone

Time	Business – City Centre Zone	Business – Metropolitan Centre Zone	Business – Town Centre Zone	Business – Mixed Use Zone
7am - 11pm	65 dB L_{Aeq}	65 dB L_{Aeq}	65dB L_{Aeq}	65dB L_{Aeq}
11pm – 7am	60dB L_{Aeq} 65dB at 63 Hz L_{Aeq} 60dB at 125 Hz L_{Aeq} 75dB L_{AFmax}	60dB L_{Aeq} 65dB at 63 Hz L_{Aeq} 60dB at 125 Hz L_{Aeq} 75dB L_{AFmax}	55dB L_{Aeq} 65dB at 63 Hz L_{eq} 60dB at 125 Hz L_{eq} 75dB L_{AFmax}	55dB L_{Aeq} 65dB at 63 Hz L_{eq} 60dB at 125 Hz L_{eq} 75dB L_{AFmax}

- (2) The 63Hz and 125Hz octave band limits do not apply to fixed mechanical plant.

E25.6.9. Noise levels between units in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone, Business – Local Centre Zone, Business – Neighbourhood Centre Zone or the Business – Mixed Use Zone

- (1) In situations where common building elements such as floors and walls connect two units in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone, Business – Local Centre Zone, Business – Neighbourhood Centre Zone or the Business – Mixed Use Zone the noise (rating) level arising from any activity measured in any unit must not exceed the levels in Table E25.6.9.1 Noise levels between units in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone, Business – Local Centre Zone, Business – Neighbourhood Centre Zone or the Business – Mixed Use Zone. below:

Table E25.6.9.1 Noise levels between units in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone, Business – Local Centre Zone, Business – Neighbourhood Centre Zone or the Business – Mixed Use Zone

Unit affected	Time	Noise level
In all units except those containing activities sensitive to noise	At all times	50dB L _{Aeq}
In bedrooms and sleeping areas within units containing activities sensitive to noise	Between 10pm and 7am in Business – Local Centre Zone and Business – Neighbourhood Centre Zone and Between 11pm and 7am in Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone and the Business – Mixed Use Zone	35dB L _{Aeq} 45dB at 63 Hz L _{eq} 40dB at 125 Hz L _{eq}
	Between 7am and 10pm in Business – Local Centre Zone and Business – Neighbourhood Centre Zone and Between 7am and 11pm in Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone and the Business – Mixed Use Zone	40dB L _{Aeq}
Other noise sensitive spaces	At all other times	40 dB L _{Aeq}
Note: Adjustments for noise containing Special Audible Characteristics will only apply to A weighted levels		

- (2) The 63Hz and 125Hz octave band limits do not apply to fixed mechanical plant.

E25.6.10. Noise levels for noise sensitive spaces in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone, Business – Local Centre Zone, Business – Neighbourhood Centre Zone or the Business – Mixed Use Zone

- (1) Noise sensitive spaces must be designed and/or insulated so that the internal noise levels do not exceed the levels in Table E25.6.10.1 Noise levels for noise sensitive spaces in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone, Business – Local Centre Zone, Business – Neighbourhood Centre Zone or the Business – Mixed Use Zone below:

Table E25.6.10.1 Noise levels for noise sensitive spaces in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone, Business – Local Centre Zone, Business – Neighbourhood Centre Zone or the Business – Mixed Use Zone

Unit affected	Time	Level
Bedrooms and sleeping areas in the Business – Local Centre Zone and in the Business – Neighbourhood Centre Zone	Between 10pm and 7am	35dB L _{Aeq} 45dB at 63 Hz L _{eq} ; and 40dB at 125 Hz L _{eq}
Bedrooms and sleeping areas in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone and the Business – Mixed Use Zone	Between 11pm and 7am	35dB L _{Aeq} 45dB at 63 Hz L _{eq} and 40dB at 125 Hz L _{eq}
Other noise sensitive spaces	At all other times	40 dBA L _{Aeq}

- (2) The levels in Table E25.6.10.1 Noise levels for noise sensitive spaces in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone, Business – Local Centre Zone, Business – Neighbourhood Centre Zone or the Business – Mixed Use Zone above must be met based on the maximum level of noise permitted by the zone or precinct standards or any adjacent zone or precinct standards.
- (3) Where a new room is constructed that is subject to Standard E25.6.10(1) (internal acoustic insulation requirement) and the noise levels in Table E25.6.10.1 Noise levels for noise sensitive spaces in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone, Business – Local Centre Zone, Business – Neighbourhood Centre Zone or the Business – Mixed Use Zone (internal design noise level) can only be complied with when doors or windows to those rooms are closed, those rooms must, as a minimum:
- (a) be constructed to ensure compliance with the noise limits in Table E25.6.10.1 Noise levels for noise sensitive spaces in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone, Business – Local Centre Zone, Business – Neighbourhood Centre Zone or the Business – Mixed Use Zone; and
 - (b) for residential dwellings be mechanically ventilated and/or cooled to achieve either:
 - (i) an internal temperature no greater than 25 degrees celsius based on external design conditions of dry bulb 25.1 degrees celsius and wet bulb 20.1 degrees celsius; or

Note 1

Mechanical cooling must be provided for all habitable rooms (excluding bedrooms) provided that at least one mechanical cooling system must service every level of a dwelling that contains a habitable room (including bedrooms).

- (ii) a high volume of outdoor air supply to all habitable rooms with an outdoor air supply rate of no less than:
 - six air changes per hour (ACH) for rooms with less than 30 per cent of the façade area glazed; or
 - 15 air changes per hour (ACH) for rooms with greater than 30 per cent of the façade area glazed; or
 - three air changes per hour for rooms with facades only facing south (between 120 degrees and 240 degrees) or where the glazing in the façade is not subject to any direct sunlight.
- (c) for all other noise sensitive spaces provide mechanical cooling to achieve an internal temperature no greater than 25 degrees celsius based on external design conditions of dry bulb 25.1 degrees celsius and wet bulb 20.1 degrees celsius; and
- (d) provide relief for equivalent volumes of spill air; and
- (e) be individually controllable across the range of airflows and temperatures by the building occupants in the case of each system; and
- (f) have a mechanical ventilation and/or a cooling system that generates a noise level no greater than L_{Aeq} 35 dB when measured 1m from the diffuser at the minimum air flows required to achieve the design temperatures and air flows in Standard E25.6.10(3)(b)(i) and (ii) above.

E25.6.11. Noise levels in the Coastal – Marina Zone [rcp/dp]

- (1) The noise (rating) level arising from an activity in the Coastal – Marina Zone measured within the boundary of any other site in this zone must not exceed the levels in Table E25.6.7.1 Noise levels in the Coastal – Marina Zone.

Table E25.6.7.1 Noise levels in the Coastal – Marina Zone

Time	Coastal – Marina Zone
All times	60dB L_{Aeq}

E25.6.12. Noise levels in the Special Purpose – Cemetery Zone or the Special Purpose – Māori Purpose Zone

- (1) The noise (rating) level and maximum noise level from any activity measured within the boundary of any site in the Special Purpose – Cemetery Zone or the Special Purpose – Māori Purpose Zone must not exceed the levels in

Table E25.6.12.1 Noise levels in the Special Purpose – Cemetery Zone or the Special Purpose – Māori Purpose Zone.

Table E25.6.12.1 Noise levels in the Special Purpose – Cemetery Zone or the Special Purpose – Māori Purpose Zone

Time	Special Purpose – Cemetery Zone or Special Purpose – Māori Purpose Zone
Monday to Saturday 7am-10pm	50 dB L _{Aeq}
Sunday 9am-6pm	
All other times	40 dB L _{Aeq} 75 dB L _{AFmax}

E25.6.13. Noise levels in the Special Purpose – Healthcare Facility and Hospital Zone

- (1) The noise (rating) level from any activity measured within the boundary of any site in the Special Purpose – Healthcare Facility and Hospital Zone must not exceed the levels in Table E25.6.13.1 Noise levels in the Special Purpose – Healthcare Facility and Hospital Zone below:

Table E25.6.13.1 Noise levels in the Special Purpose – Healthcare Facility and Hospital Zone

Time	Special Purpose – Health Care Facility and Hospital Zone
Monday to Saturday 7am-10pm	55 dB L _{Aeq}
Sunday 9am-6pm	
All other times	45 dB L _{Aeq} 75 dB L _{AFmax}

Noise levels for activities between zones

E25.6.14. Noise levels at the coastal interface [rcp/dp]

- (1) The noise (rating) level generated by any activity in the coastal marine area or on a lake or river must not exceed the levels in Table E25.6.14.1 Noise levels at the coastal interface when measured within the boundary of a site in a residential zone or notional boundary of any site in the Rural – Rural Production Zone, Rural – Mixed Rural Zone, Rural – Rural Coastal Zone; Rural – Rural Conservation Zone, Rural – Countryside Living Zone, Rural – Waitākere Foothills Zone and Rural – Waitākere Ranges Zone.

Table E25.6.14.1 Noise levels at the coastal interface

Time	Noise level
7am-10pm	50dB L _{Aeq}
10pm-7am	40dB L _{Aeq} 75dB L _{AFmax}

(2) The noise levels in Standard E25.6.14(1) above do not apply to:

- (a) the operational requirements of vessels (including cargo vessels, tugs, passenger liners, naval vessels and commercial fishing vessels); and
- (b) temporary activities in E40 Temporary activities.

E25.6.15. Rural – Mixed Rural Zone, Rural – Rural Production Zone, Rural – Rural Coastal Zone or Future Urban Zone interface

(1) The noise (rating) level and maximum noise level from any activity in the Rural – Mixed Rural Zone, Rural – Rural Production Zone, Rural – Rural Coastal Zone or Future Urban Zone measured within the boundary of any site in a residential zone must not exceed the levels in Table E25.6.15.1 Noise levels at the Rural – Mixed Rural Zone, Rural – Rural Production Zone, Rural – Rural Coastal Zone or Future Urban Zone interface below:

Table E25.6.15.1 Noise levels at the Rural – Mixed Rural Zone, Rural – Rural Production Zone, Rural – Rural Coastal Zone or Future Urban Zone interface

Time	Noise level
Monday to Saturday 7am-10pm	55dB L _{Aeq}
Sunday 9am-6pm	
All other times	45dB L _{Aeq} 75dB L _{AFmax}

(2) Standard E25.6.15(1) above does not apply to:

- (a) animal noise on farms unless they are confined within a building or enclosure on a permanent or semi-permanent basis; or
- (b) the use of mobile agricultural horticultural or forestry vehicles or machinery, or other mobile or portable agricultural, horticultural or forestry equipment; or

Note 1

The operator of such vehicles or machinery is required by the Resource Management Act 1991 to adopt the best practicable option to ensure that noise emissions do not exceed a reasonable level, which will depend on the time they are used, how loud they are, how long it is used for and how often it is used near dwellings.

- (c) the use of post-harvest facilities including vehicle access ways and milking sheds set back at least 100m from any residential zone.

**E25.6.16. Rural – Rural Conservation Zone, Rural – Countryside Living Zone
Rural – Waitākere Foothills Zone or Rural – Waitākere Ranges Zone
interface**

- (1) The noise (rating) level and maximum noise level from any activity in the Rural – Rural Conservation Zone, Rural – Countryside Living Zone, Rural – Waitākere Foothills Zone or the Rural – Waitākere Ranges Zone measured within the boundary of any site in a residential zone must not exceed the levels in Table E25.6.16.1 Noise levels at the Rural – Rural Conservation Zone, Rural – Countryside Living Zone, Rural – Waitākere Foothills Zone or the Rural – Waitākere Ranges Zone.

Table E25.6.16.1 Noise levels at the Rural – Rural Conservation Zone, Rural – Countryside Living Zone, Rural – Waitākere Foothills Zone or the Rural – Waitākere Ranges Zone

Time	Noise level
Monday to Saturday 7am-10pm	50dB L _{Aeq}
Sunday 9am-6pm	
All other times	40dB L _{Aeq} 75dB L _{AFmax}

- (2) Standard E25.6.16(1) above does not apply to:
- (a) animal noise on farms unless they are confined within a building or enclosure on a permanent or semi-permanent basis; or
 - (b) the use of mobile agricultural horticultural or forestry vehicles or machinery, or other mobile or portable agricultural, horticultural or forestry equipment; or

Note 1

The operator of such vehicles or machinery is required by the Resource Management Act 1991 to adopt the best practicable option to ensure that noise emissions do not exceed a reasonable level, which will depend on the time they are used, how loud they are, how long it is used for and how often it is used near dwellings.

- (c) the use of post-harvest facilities including vehicle access ways and milking sheds set back at least 100m from any residential zone.

E25.6.17. Open Space – Sport and Active Recreation Zone interface

- (1) The noise (rating) level and maximum noise level arising from any recreational activity in the Open Space – Sport and Active Recreation Zone measured within the boundary of a site in a residential zone or notional boundary of a site in a rural zone must not exceed the levels in Table E25.6.17.1 Noise levels at the Open Space – Sport and Active Recreation Zone interface below:

Table E25.6.17.1 Noise levels at the Open Space – Sport and Active Recreation Zone interface

Time	Noise level
Monday to Saturday 7am-10pm	55dB L_{Aeq} Except that for a cumulative period of: (i) 3 hours per day between 7am and 9.30pm Monday to Friday; and (ii) 6 hours between 7am and 10pm on Saturdays. the noise level must not exceed 60dB L_{Aeq}
Sundays and Public Holidays 9am to 6pm outside the daylight saving period	55dB L_{Aeq} Except that for a cumulative period of 3 hours between 10am and 3pm on Sundays the noise level must not exceed 60dB L_{Aeq}
Sundays and Public Holidays 8am to 7pm during the daylight saving period	55dB L_{Aeq} Except that for a cumulative period of 3 hours between 10am and 3pm Sundays the noise level must not exceed 60dB L_{Aeq}
All other times	40dB L_{Aeq} 55dB L_{eq} at 63 Hz 50dB L_{eq} at 125 Hz 75dB L_{AFmax}

Note 1

Compliance with the lower noise limit of 40dB L_{Aeq} applying at all other times in Table E25.6.17.1 Noise levels at the Open Space – Sport and Active Recreation Zone interface may preclude intense, noisy activities or activities involving teams or groups from being undertaken where the receivers of noise are close to boundaries.

- (2) The noise (rating) level and maximum noise level from the use of any voice or music amplification system associated with recreational activity in the Open Space – Sport and Active Recreation Zone measured within the boundary of a site in a residential zone or notional boundary of a site in a rural zone must not exceed the levels in Table E25.6.17.2 Noise levels from any voice or music amplification system associated with recreational activity on land zoned Open Space – Sport and Active Recreation Zone below:

Table E25.6.17.2 Noise levels from any voice or music amplification system associated with recreational activity on land zoned Open Space – Sport and Active Recreation Zone

Time	Noise level
Monday to Saturday 7am-10pm	50dB $L_{Aeq(5min)}$
Sunday and Public Holidays 9am-6pm	
All other times	40dB $L_{Aeq(5min)}$ 55dB $L_{eq(5min)}$ at 63 Hz 50dB $L_{eq(5min)}$ at 125 Hz 75dB L_{AFmax}

- (a) No five minute measurement may exceed the stated limit.

E25.6.18. Open Space – Conservation Zone, Open Space – Informal Recreation Zone, Open Space – Civic Spaces Zone or Open Space – Community Zone interface

- (1) The noise (rating) level and maximum noise level from any activity in the Open Space – Conservation Zone, Open Space – Informal Recreation Zone, Open Space – Civic Spaces Zone or Open Space – Community Zone when measured within the boundary of a site in a residential zone or notional boundary of a site in a rural zone must not exceed the levels in Table E25.6.18.1 Noise levels at the Open Space – Conservation Zone, Open Space – Informal Recreation Zone, Open Space – Civic Spaces Zone or Open Space – Community Zone interface below:

Table E25.6.18.1 Noise limits at the Open Space – Conservation Zone, Open Space – Informal Recreation Zone, Open Space – Civic Spaces Zone or Open Space – Community Zone interface

Time	Noise level
Monday to Saturday 7am-10pm	50dB L _{Aeq}
Sunday 9am-6pm	
All other times	40dB L _{Aeq} 75dB L _{AFmax}

E25.6.19. Business zones interface

- (1) The noise (rating) and maximum noise level from any activity in the business zones must not exceed the levels in Table E25.6.19.1 Noise levels at the business zone interface when measured within the boundary of a site in a residential zone or within the notional boundary of property in a rural zone.

Table E25.6.19.1 Noise levels at the business zone interface

Time	Noise level
Monday to Saturday 7am-10pm	55dB L _{Aeq}
Sunday 9am-6pm	
All other times	45dB L _{Aeq} 60dB L _{eq} at 63 Hz 55dB L _{eq} at 125 Hz 75dB L _{AFmax}


- (2) These noise limits in Standard E25.6.19(1) above do not apply to any of the following:
- (a) the noise from vehicles moving on roads controlled by Auckland Council or Auckland Transport; or
 - (b) the noise affecting 11, 13, and 15 Harrison Road as generated on the Fulton Hogan sites at 7 Reliable Way (Lot 2, DP 114222, CT NA65A/209) and 4 Reliable Way Mt Wellington (Lot 3, DP 363738, CT 259289). Instead, the noise (rating) level arising from the Fulton Hogan sites must comply with a limit of 60dB L_{Aeq} when measured within the boundary of 11, 13 or 15 Harrison Road; or
 - (c) the noise affecting the sites identified in Table E25.6.19.2 Affected sites and on Figure E25.6.19.1 Affected sites as generated on the DB Waitemata Breweries site and 3 Bairds Road, Ōtahuhu (being PT Lot 4 DP 22498, Lot 1, DP 29149, PT Lot 4 DP 15832, PT Lot 2 DP 31817, PT Lot 9 DP 26107, Lot 1 DP 31104, PT Lot 10 DP 7281 all on CT 443069). Instead, the noise (rating) level arising from the DB Waitemata Breweries site must comply with a limit of 65dB L_{Aeq} with a maximum noise limit of

90dB L_{AFmax} applying only between the hours of 10pm and 7am when measured within the boundary of the sites identified in Table E25.6.19.2 Affected sites and shown on Figure E25.6.19.1 Affected sites below:

Table E25.6.19.2 Affected sites

Lot 1 DP 205759	Lot 10 DP 205759
Lot 14 DP 205759	Lot 2 DP 205759
Lot 22 DP 205759	Lot 4 DP 205759
Lot 25 DP 205759	Lot 8 DP 205759
Lot 26 DP 205759	Lot 17 DP 205759
Lot 31 DP 205759	Lot 12 DP 205759
Lot 304 DP 205759	Lot 11 DP 205759
Lot 6 DP 205759	Lot 15 DP 205759
Lot 302 DP 205759	Lot 300 DP 205759
Lot 301 DP 205759	Lot 24 DP 205759
Lot 18 DP 205759	Lot 28 DP 205759
Lot 19 DP 205759	Lot 34 DP 205759
Lot 23 DP 205759	Lot 35 DP 205759
Lot 29 DP 205759	Lot 14 DP 335896
Lot 33 DP 205759	Lot 18 DP 335896
Lot 13 DP 205759	Lot 7 DP 335896
Lot 16 DP 205759	Lot 8 DP 335896
Lot 7 DP 205759	Lot 9 DP 335896
Lot 9 DP 205759	Lot 13 DP 335896
Lot 3 DP 205759	Lot 15 DP 335896
Lot 5 DP 205759	Lot 16 DP 335896
Lot 21 DP 205759	Lot 17 DP 335896
Lot 27 DP 205759	Lot 31 DP 341162
Lot 30 DP 205759	Lot 28 DP 341162
Lot 32 DP 205759	Lot 29 DP 341162
Lot 303 DP 205759	Lot 30 DP 341162
Lot 36 DP 205759	Lot 100 DP 341162
Lot 37 DP 205759	Lot 27 DP 341162

Figure E25.6.19.1 Affected sites



E25.6.20. Noise levels at the Coastal – Marina Zone interface

- (1) The noise (rating) levels and maximum noise level from any activity on land in the Coastal – Marina Zone must not exceed the levels in Table E25.6.20.1 Noise levels at the Coastal Marina Zone interface when measured within the boundary of a site in a residential zone or within the notional boundary of property in a rural zone.

Table E25.6.20.1 Noise levels at the Coastal – Marina Zone interface

Time	Noise level
Monday to Saturday 7am-10pm	55dB L _{Aeq}
Sunday 9am-6pm	
All other times	45dB L _{Aeq} 60dB L _{eq} at 63 Hz 55dB L _{eq} at 125 Hz 75dB L _{AFmax}

- (2) The noise levels in Standard E25.6.20(1) above do not apply to the noise from vehicles moving on roads controlled by Council or Auckland Transport.

E25.6.21. Schools interface

- (1) The noise (rating) level and maximum noise level from any neighbouring activity measured within the boundary of any school not located in the Special Purpose – School Zone must not exceed the levels in Table E25.6.21.1 Noise levels from any neighbouring activity measured within the boundary of any school not located in a Special Purpose – School Zone.

Table E25.6.21.1 Noise levels from any neighbouring activity measured within the boundary of any school not located in a Special Purpose – School Zone:

Time	Noise level
Monday to Saturday 7am-10pm	55dB L _{Aeq}
Sunday 9am-6pm	
All other times	45dB L _{Aeq} 75dB L _{AFmax}

E25.6.22. All other zone interfaces

- (1) Except as provided for in Standards E25.6.14 to E25.6.21 above, where noise generated by any activity on a site in one zone is received by any activity on a site in a different zone, the activity generating the noise must comply with the noise limits and standards of the zone at the receiving site.

*Noise arising from specific activities***E25.6.23. Noise levels for care centres for a childcare centre, creche, kindergarten, kohanga reo, play centre, play group, early childhood learning service or an after school care centre**

- (1) The noise (rating) level arising from any care centres for a childcare centre, creche, kindergarten, kohanga reo, play centre, play group, early childhood learning service or an after school care centre in any zone when measured within the boundary of any site in a residential zone must not exceed the levels in Table E25.6.23.1 Noise levels for care centres for a childcare centre, creche, kindergarten, kohanga reo, play centre, play group, early childhood learning service or an after school care centre unless the relevant zone in which the care centres for a childcare centre, creche, kindergarten, kohanga reo, play centre, play group, early childhood learning service or an after school care centre is located provides for higher levels.

Table E25.6.23.1 Noise levels for care centres for a childcare centre, creche, kindergarten, kohanga reo, play centre, play group, early childhood learning service or an after school care centre

Time	Noise level
Monday to Friday 7am-6pm	55dB L _{Aeq}
All other times	40dB L _{Aeq} 75dB L _{AFmax}

E25.6.24. Noise levels for a primary school, intermediate school, secondary school or tertiary education facility

- (1) The noise (rating) level arising from the operation of a primary, intermediate school, secondary school or tertiary education facility must comply with the noise levels in Table E25.6.24.1 Noise levels for a primary school, intermediate school, secondary school or tertiary education facility when measured within the boundary of any residentially zoned site.

Table E25.6.24.1 Noise levels for a primary school, intermediate school, secondary school or tertiary education facility

Time	Noise level
Monday to Saturday 7am to 10pm	55dB L _{Aeq}
Sunday 9am to 6pm	
All other times	45dB L _{Aeq} 75dB L _{AFmax}

Note 1

Compliance with the noise levels of 45dB L_{Aeq} and 75dB L_{AFmax} applying at all other times in Table E25.6.24.1 Noise levels for a primary school, intermediate school, secondary school or tertiary education facility may mean that functions, events, and other activities utilising buildings, car parks, accessways and open space proximate to any activity sensitive to noise may need to be restricted in terms of finishing time or noise level.

- (2) These noise limits do not apply to noise from school sports and school recreational activities occurring between 8am and 6pm Monday to Saturday.

E25.6.25. Noise levels for wind turbines or wind farms

- (1) At any wind speed, the $L_{A90 (10min)}$ sound level from a wind turbine generator or wind farm must not exceed the background sound level by more than 5dB, or a level of 40dB $L_{A90 (10min)}$ whichever is the greater when measured within the notional boundary on any property which is a noise sensitive location as defined in New Zealand Standard 6808: 2010 Acoustics – Wind farm noise.
- (2) The noise level generated by wind farms must be measured and assessed in accordance with New Zealand Standard 6808:2010 Acoustics – Wind farm noise.

E25.6.26. Noise levels for electricity generators

- (1) The noise (rating) level and maximum noise level arising from the use of any electricity generator in a rural zone or a residential zone powered by an internal combustion engine measured within the boundary of any site in a residential zone or the notional boundary of any site in a rural zone must not exceed the levels in Table E25.6.26.1 Noise levels for electricity generators.

Table E25.6.26.1 Noise levels for electricity generators

Time	Noise level
7am to 10pm	40dB L_{Aeq}
10pm to 7am	30dB L_{Aeq} 75dB L_{AFmax}

- (2) Standard E25.6.26(1) does not apply to generators in use prior to the 30 September 2013. For generators established on or before 30 September 2013 the noise limits for the relevant zone or zone interface apply.

*Construction noise***E25.6.27. Construction noise levels in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone**

- (1) Noise from construction activities in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone must not exceed the levels in Table E25.6.27.1 Construction noise levels for activities sensitive to noise in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone when measured 1m from the façade of any building that contains an activity sensitive to noise that is occupied during the works.

Table E25.6.27.1 Construction noise levels for activities sensitive to noise in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone

Time of week	Time Period	Maximum noise level (dBA)	
		L _{eq}	L _{max}
Weekdays	6:30am - 7:30am	60	75
	7:30am - 6:00pm	75	90
	6:00am - 8:00pm	70	85
	8:00pm - 6:30am	45	75
Saturdays	6:30am - 7:30am	45	75
	7:30am - 6:00pm	75	90
	6:00am - 8:00pm	45	75
	8:00pm - 6:30am	45	75
Sundays and public holidays	6:30am - 7:30am	45	75
	7:30am - 6:00pm	55	85
	6:00pm - 8:00pm	45	75
	8:00pm - 6:30am	45	75

- (2) Noise from construction activities in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone must not exceed the levels in Table E25.6.27.2 Construction noise levels for noise affecting any other activity when measured 1m from the façade of any other building that is occupied during the works.

Table E25.6.27.2 Construction noise levels for noise affecting any other activity

Time Period	Maximum noise levels Leq dBA
7:30am – 6:00pm	75
6:00pm – 7:30am	80

- (3) For a project involving a total duration of construction work that is less than 15 calendar days, the noise levels in Table E25.6.27.1 Construction noise levels for activities sensitive to noise in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone and Table E25.6.27.2 Construction noise levels for noise affecting any other activity above may be increased by 5dB in all cases.
- (4) For a project involving a total duration of construction work that is more than 20 weeks the noise limits in Table E25.6.27.1 Construction noise levels for activities sensitive to noise in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone and Table E25.6.27.2 Construction noise levels for noise affecting any other activity above may be decreased by 5dB in all cases.

E25.6.28. Construction noise levels in the Business – City Centre Zone and the Business – Metropolitan Centre Zone

- (1) Construction activities in the Business – City Centre Zone and the Business – Metropolitan Centre Zone must comply with Standard E25.6.27(1) above for any receiver not in a Business – City Centre Zone or a Business – Metropolitan Centre Zone and must not exceed the levels in Table E25.6.28.1 Construction noise levels for construction less than 15 consecutive calendar days duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone and Table E25.6.28.2 Construction noise levels for construction of 15 consecutive calendar days or more duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone when measured for any 30 minute period 1m from the façade of any building in the Business – City Centre Zone or the Business – Metropolitan Centre Zone that is occupied during the work.

Table E25.6.28.1 Construction noise levels for construction less than 15 consecutive calendar days duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone

Construction of less than 15 consecutive calendar days duration (total duration of works)		
Time	L_{Aeq}(30 min)	L_{AFmax}
Monday to Friday 6.30am - 10.30pm	80 dB	90 dB
Saturday 7am - 11pm	85 dB	90 dB
Sunday 9am - 7pm	80 dB	90 dB
All other times (night time)	60 dB	75 dB
All other times in the City Centre Residential Precinct and the Learning Precinct	55 dB	75 dB

Table E25.6.28.2 Construction noise levels for construction of 15 consecutive calendar days or more duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone

Construction of 15 consecutive calendar days or more (total duration of works)		
Time	L_{Aeq(30 min)}	L_{AFmax}
Monday to Friday 6.30am-10.30pm	75 dB	90 dB
Saturday 7am-11pm	80 dB	90 dB
Sunday 9am-7pm	65 dB	85 dB
All other times (night time)	60 dB	75 dB
All other times in the City Centre Residential Precinct and the Learning Precinct	55 dB	75dB

Where external measurement of construction noise is impractical or inappropriate, the upper limits for the noise measured inside the building will be 20dB less than the relevant levels in Table E25.6.28.1 Construction noise levels for construction less than 15 consecutive calendar days duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone and Table E25.6.28.2 Construction noise levels for construction of 15 consecutive calendar days or more duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone above.

E25.6.29. Construction noise levels for work within the road

- (1) Noise from any construction, maintenance and demolition activities in the road must meet the relevant noise levels in the following relevant table:
 - (a) Table E25.6.27.1 Construction noise levels for activities sensitive to noise in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (b) Table E25.6.27.2 Construction noise levels for noise affecting any other activity; or
 - (c) Table E25.6.28.1 Construction noise levels for construction less than 15 consecutive calendar days duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (d) Table E25.6.28.2 Construction noise levels for construction of 15 consecutive calendar days or more duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone.

- (2) The noise levels specified in Standard E25.6.29(1) above do not apply to unplanned repair or maintenance works or planned works in the road between the hours of 10pm and 7am where:
- (a) the number of nights where the noise generated by the works exceeds the relevant noise levels in the following tables:
 - (i) Table E25.6.27.1 Construction noise levels for activities sensitive to noise in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (ii) Table E25.6.27.2 Construction noise levels for noise affecting any other activity; or
 - (iii) Table E25.6.28.1 Construction noise levels for construction less than 15 consecutive calendar days duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (iv) Table E25.6.28.2 Construction noise levels for construction of 15 consecutive calendar days or more duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone;at any one receiver is 3 nights or less; and
 - (b) the works cannot practicably be carried out during the day or because the road controlling authority requires this work to be done at night time; or
 - (c) because of the nature of the works the noise produced cannot be practicably be made to comply with the relevant noise levels of the following tables:
 - (i) Table E25.6.27.1 Construction noise levels for activities sensitive to noise in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (ii) Table E25.6.27.2 Construction noise levels for noise affecting any other activity; or
 - (iii) Table E25.6.28.1 Construction noise levels for construction less than 15 consecutive calendar days duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (iv) Table E25.6.28.2 Construction noise levels for construction of 15 consecutive calendar days or more duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (d) for planned works, a copy of the works access permit issued by Auckland Transport or approval from the New Zealand Transport Agency is provided to the Council five days prior to work commencing; or

- (e) for minor planned works a construction noise and vibration management plan is provided to the Council no less than five days prior to the works commencing in accordance with the applicable provisions of Standard E25.6.29(5) below.
- (3) The noise levels specified in Standard E25.6.29(1) above do not apply to unplanned repair or maintenance works or planned works in the road between the hours of 7am and 10pm where:
- (a) the number of days where the noise generated by the works exceeds the relevant noise levels in the following tables:
 - (i) Table E25.6.27.1 Construction noise levels for activities sensitive to noise in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (ii) Table E25.6.27.2 Construction noise levels for noise affecting any other activity; or
 - (iii) Table E25.6.28.1 Construction noise levels for construction less than 15 consecutive calendar days duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (iv) Table E25.6.28.2 Construction noise levels for construction of 15 consecutive calendar days or more duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone;at any one receiver is 10 or less; or
 - (b) because of the nature of the works and the proximity of receivers the noise generated cannot practicably be made to comply with the relevant noise levels of the following tables:
 - (i) Table E25.6.27.1 Construction noise limits for activities sensitive to noise in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (ii) Table E25.6.27.2 Construction noise limits for noise affecting any other activity; or
 - (iii) Table E25.6.28.1 Construction noise limits for construction less than 15 consecutive calendar days duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (iv) Table E25.6.28.2 Construction noise limits for construction of 15 consecutive calendar days or more duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (c) for planned works, a copy of the works access permit issued by Auckland Transport or approval from the New Zealand Transport Agency is provided to the Council five days prior to work commencing; or

- (d) for planned works where the works will take more than 8 hours to complete a construction noise and vibration management plan is provided to the Council no less than five days prior to the works commencing in accordance with the applicable provisions of Standard E25.6.29(5) below.
- (4) The noise levels specified in Standard E25.6.29(1) do not apply to road rehabilitation works that comprise the substantial removal and replacement of the road structural base and pavement in the road where:
- (a) the number of nights where the noise generated by the works exceeds the relevant noise levels in the following tables:
- (i) Table E25.6.27.1 Construction noise levels for activities sensitive to noise in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (ii) Table E25.6.27.2 Construction noise levels for noise affecting any other activity; or
 - (iii) Table E25.6.28.1 Construction noise levels for construction less than 15 consecutive calendar days duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (iv) Table E25.6.28.2 Construction noise levels for construction of 15 consecutive calendar days or more duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone;
- at any one receiver is 20 days or less; and
- (b) milling, concrete cutting, percussive demolition are completed by 10.30pm; and
- (c) the works cannot practicably be carried out during the day or because the road controlling authority requires this work to be done at night time; and
- (d) because of the nature of the works the noise produced cannot be practicably be made to comply with the relevant noise levels of the following tables:
- (i) Table E25.6.27.1 Construction noise levels for activities sensitive to noise in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (ii) Table E25.6.27.2 Construction noise levels for noise affecting any other activity; or
 - (iii) Table E25.6.28.1 Construction noise levels for construction less than 15 consecutive calendar days duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or

- (iv) Table E25.6.28.2 Construction noise levels for construction of 15 consecutive calendar days or more duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone; and
 - (e) a copy of the works access permit issued by Auckland Transport or approval from the New Zealand Transport Agency is provided to the Council five days prior to work commencing; and
 - (f) a construction noise and vibration management plan is provided to the Council no less than five days prior to the works commencing in accordance with the applicable provisions of Standard E25.6.29(5) below.
- (5) A construction noise and vibration management plan must be prepared by a suitably qualified and experienced person and include the following:
- (a) details of the community consultation to be undertaken to advise the occupiers of properties located within 100m of the proposed works of all of the following:
 - (i) the area affected by the work;
 - (ii) why the work is required to be undertaken at night (where relevant);
 - (iii) the times and days when the noise and vibration is likely to be generated;
 - (iv) a contact name and number of the works supervisor who can be contacted if any issues arise; and
 - (v) how noise and vibration complaints will be managed and responded to;
 - (b) a description of the works and its duration, anticipated equipment to be used and the processes to be undertaken; and
 - (c) identification of the best practicable options that will be undertaken to mitigate and minimise any noise being produced that is likely to exceed the relevant levels of the following tables:
 - (i) Table E25.6.27.1 Construction noise levels for activities sensitive to noise in all zones except the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or
 - (ii) Table E25.6.27.2 Construction noise levels for noise affecting any other activity; or
 - (iii) Table E25.6.28.1 Construction noise levels for construction less than 15 consecutive calendar days duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone; or

(iv) Table E25.6.28.2 Construction noise levels for construction of 15 consecutive calendar days or more duration in the Business – City Centre Zone and the Business – Metropolitan Centre Zone.

(6) For the purpose of Standards E25.6.29(1) to E25.6.29(4) above:

- (a) planned work means work that has been planned to take place at least seven days before the work commences; and
- (b) the measurement and assessment of all construction noise must be in accordance with New Zealand Standard NZS 6803:1999 Acoustics – Construction noise.

Vibration

E25.6.30. Vibration

- (1) Construction and demolition activities must be controlled to ensure any resulting vibration does not exceed:
 - (a) the limits set out in German Industrial Standard DIN 4150-3 (1999): Structural vibration – Part 3 Effects of vibration on structures when measured in accordance with that Standard on any structure not on the same site; and
 - (b) the limits in Table E25.6.30.1 Vibration limits in buildings in any axis when measured in the corner of the floor of the storey of interest for multi-storey buildings, or within 500mm of ground level at the foundation of a single storey building.

Table E25.6.30.1 Vibration limits in buildings

Receiver	Period	Peak Particle Velocity Limit millimetres/second
Occupied activity sensitive to noise	Night-time 10pm to 7am	0.3 mm/s
	Daytime 7am to 10pm	2 mm/s
Other occupied buildings	At all times	2 mm/s

Works generating vibration for three days or less between the hours of 7am to 6pm may exceed the limits in Table E25.6.30.1 Vibration limits in buildings above, but must comply with a limit of 5mm/s peak particle velocity in any axis when measured in the corner of the floor of the storey of interest for multi-storey buildings, or within 500mm of ground level at the foundation of a single storey building, where:

- (i) all occupied buildings within 50m of the extent of the works generating vibration are advised in writing no less than three days prior to the vibration-generating works commencing; and
 - (ii) the written advice must include details of the location of the works, the duration of the works, a phone number for complaints and the name of the site manager.
- (2) Permanently installed stationary vibrating, reciprocating and rotating machinery and all piping, ducting and other equipment attached to such machinery must be installed and maintained so that any resulting vibration does not exceed the limits of Table E25.6.30.2 Vibration levels for stationary machinery when measured in any occupied room of any building on another site or in any occupied unit under different ownership from the source of the vibration. Vibration must be measured in accordance with ISO 2631-2:2003 Mechanical vibration and shock – Evaluation of human exposure to whole-body vibration – Part 2: Vibration in buildings (1Hz to 80Hz):

Table E25.6.30.2 Vibration levels for stationary machinery

Affected occupied building or area	Time of day	Maximum vibration level in root mean square velocity (mm/s) between 8 and 80Hz
Noise sensitive spaces	7am-10pm	0.20
Bedrooms and sleeping areas only within activities sensitive to noise	10pm-7am	0.14

Blasting

E25.6.31. Noise levels for blasting

- (1) The noise created by the use of explosives for any blasting activity measured at the boundary of the site on which the explosives are used must not exceed a peak sound pressure of 120 dB (L_{zpeak}).
- (2) The noise created by the use of explosives for construction activities must not exceed a peak sound pressure level of 120dBC measured 1m from the façade of any occupied building.

Helicopter noise

E25.6.32. Noise levels for helicopters take-off or landing

- (1) The take-off or landing of a helicopter on any site except for emergency services must not exceed L_{dn} 50dB or 85dB L_{AFmax} measured within the boundary or the notional boundary of any adjacent site containing activities sensitive to noise and L_{dn} 60dBA within the boundary of any other site.

Transport noise

E25.6.33. Noise levels for traffic from new and altered roads

- (1) All new roads and all altered roads that are within the scope of New Zealand Standard NZS 6806: 2010 Acoustics – Road traffic noise – New and altered roads must comply with the requirements of New Zealand Standard NZS 6806: 2010 Acoustics – Road traffic noise – New and altered roads.

E25.7. Assessment – controlled activities

There are no controlled activities in this section.

E25.8. Assessment – restricted discretionary activities

E25.8.1. Matters of discretion

The Council will restrict its discretion to all of the following matters when assessing a restricted discretionary resource consent application:

- (1) for noise and vibration:
- (a) the effects on adjacent land uses particularly activities sensitive to noise; and
 - (b) measures to avoid, remedy or mitigate the adverse effects of noise.
- (2) for internal noise levels of noise sensitive spaces in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone, Business – Local Centre Zone, Business – Neighbourhood Centre Zone or the Business – Mixed Use Zone:
- (a) reverse sensitivity effects; and
 - (b) alternative temperature control solutions.

E25.8.2. Assessment criteria

The Council will consider the relevant assessment criteria for restricted discretionary activities from the list below:

- (1) for noise and vibration:
- (a) whether activities can be managed so that they do not generate unreasonable noise and vibration levels on adjacent land uses particularly activities sensitive to noise;
 - (b) the extent to which the noise or vibration generated by the activity:
 - (i) will occur at times when disturbance to sleep can be avoided or minimised; and
 - (ii) will be compatible with activities occurring or allowed to occur in the surrounding area; and
 - (iii) will be limited in duration, or frequency or by hours of operation; and

- (iv) will exceed the existing background noise and vibration levels in that environment and the reasonableness of the cumulative levels; and
 - (v) can be carried out during daylight hours, such as road works and works on public footpaths.
- (c) the extent to which the effects on amenity generated by vibration from construction activity:
- (i) will be mitigated by written advice of the activity to adjacent land uses prior to the activity commencing; and
 - (ii) can be mitigated by monitoring of structures to determine risk of damage to reduce occupant concern; and
 - (iii) can be shown to have been minimised by the appropriate assessment of alternative options; and
 - (iv) are reasonable taking into account the level of vibration and the duration of the activity (where levels of 10mm/s peak particle velocity may be tolerated only for very brief periods).
- (d) whether the measures to minimise the noise or vibration generated by the activity represent the best practicable option.
- (2) for works in the road or rail corridor:
- (a) whether the effects on amenity values and sleep quality generated by construction activity in the road or rail corridor are reasonable taking into account the background noise levels.
- (3) for reverse sensitivity effects:
- (a) whether the activity or infringement proposed will unduly constrain the operation of existing activities (excluding construction or demolition activities).
- (4) for noise in the Business – City Centre Zone, Business – Metropolitan Centre Zone, Business – Town Centre Zone, Business – Local Centre Zone, Business – Neighbourhood Centre Zone or the Business – Mixed Use Zone:
- (a) in addition to the assessment criteria in E25.8.2(1) above, all of the following will be considered:
 - (i) the background noise at the affected receivers and the extent to which this is proposed to be exceeded;
 - (ii) the level of existing sound insulation (where that information is available) and ventilation options for affected receivers existing as at the date of notification of the Plan; and
 - (iii) the frequency and duration of the exceedance.
- (5) for alternative temperature control solutions:

- (a) whether alternative solutions such as passive or mixed-mode cooling can provide a sufficient thermal comfort level that can be maintained having regard to ASHRAE (US) Standard 55:2013 - Thermal environmental conditions for human occupancy, CIBSE (UK) Technical Memorandum TM52:2013 – The limits of thermal comfort: avoiding overheating in European buildings, BS EN 15251:2007 – Indoor environmental input parameters for design and assessment of energy performance of buildings addressing indoor air quality, thermal environment, lighting and acoustics.

E25.9. Special information requirements

There are no special information requirements in this section.